

Mini-Jacquard Single-Jersey with 3-Way-Technique

S3P148
S3P172



experience makes the difference



Terrot Mini-Jacquard machines with 3-Way-Technique for frequent and rapid pattern change

Frame

- Standard C-frame for 500 mm fabric rolls
- Industrial C-frame for 800 and 1050 mm fabric rolls
- Oil bath for cylinder bearing
- Hand levers
- Uniwave spray oiler
- Pulsonic 5 oiler

Needles

- 1 type of cylinder needle

Needle selection

- Terrot selection mechanism with only one line of pattern levers for 3-Way-Technique KNIT - TUCK - MISS

Cam parts

- Exchange cams for 3 positions KNIT-TUCK-MISS
- Mesh conversion kit

Fabric take-down

- Motorized fabric take-down with 3-roller and automatic winding up device and adjustment rings, fabric free of pressure
- Cadratex fabric spreader
- Fabric folding device
- Fabric basket
- Rotating cutting device

Yarn feeding

- 2 ring, 4 step drives
- Positive feeding unit type MPF
- Standard tube creel with reserve pins
- Ceramic yarn carriers
- Elastomeric plating equipment with MER
- Various creel versions

Electric

- Frequency controlled drive (AC) 4 KW
- Digital Inverter
- Control voltage 24 V

Control

- Central processor unit with display
- 5-shift counter
- Digital revolution counter
- Fabric roll size counter

Additional

- Internet and web adapter
- Needle bed lighting
- Venticleaner
- Electronic needle detectors

Pattern preparation

- Design software MET 5000

- Standard
- Options

TYPE	S3P148			
Diameter in inch		30"	34"	
No. of feeders		48	54	
Gauges E	6 - 12 / 14-28*			

TYPE	S3P172			
Diameter in inch	26"	30"	34"	38"**
No. of feeders	62	72	84	90
Gauges E	12-30 (32*)			

* on request



S3P172 - Knitting head



S3P172 S3P172 - Fabric take-down device