



S4F348 | S6F348

Terrot Single Striper machines with 4- or 6-colour stripers and up to 4 needle tracks provide decisive advantage in production and huge application variety

Frame

- Standard C-frame for 500 mm fabric rolls
- Industrial C-frame for 800 and 1050 mm fabric rolls
- Gauge conversion "Quick Change"
- Oil bath for cylinder bearing and striper drive system
- Hand levers
- Uniwave spray oiler
- Pulsonic 5 oiler

Needles

- Up to 4 needle tracks in cylinder

Cam parts

- Exchange cams for 3 positions KNIT - TUCK - MISS

Fabric take-down

- Motorized fabric take-down with 3-roller and automatic winding up device and adjustment rings, fabric free of pressure
- Cadratex fabric spreader
- Fabric folding device
- Fabric basket

Yarn feeding

- 1 ring, 2 step drives
- Friction feeder MJS on 1 ring (S4F348)
- Friction feeder MJS on 2 rings (S6F348)
- Elastomeric plating equipment with MER
- Standard creel with reserve pins
- Various creel versions

Electric

- Frequency controlled drive (AC) 4 KW
- Digital Inverter
- Control voltage 24 V

Control

- Central processor unit with display
- Striper controller
- Digital revolution counter
- Fabric roll size counter

Additional

- Internet and web adapter
- Needle bed lighting
- Venticleaner
- Electronic needle detectors
- Standard Options

Front page: Model S4F348

TYPE	S4F348 S6F348		
Diameter in inch	26"	30"	34"
No. of feeders	42	48	48
Gauges E	12-28		
Needle tracks	up to 4		
Speed up to	1.05 m/s 1.20 m/s*		

* with Speed Up Function

0

0


0



S4F348 - Knitting head



S6F348 - 6 colour striper unit



S4F348 - 4 colour striper unit

Subject to technical changes. Illustrations may show accessories that are not included in the standard version.

Terrot GmbH Paul-Gruner-Straße 72B 09120 Chemnitz Germany

Phone: +49 371 5201-0 | Fax: +49 371 5201-200

email: info@terrot.de | www.terrot.de